

DIGITAL PROJECTOR | SX920



Features


- Native XGA (1024 x 768) resolution
- 5,000 ANSI lumens
- 3,000:1 high contrast ratio
- Vertical lens shift
- 1.6x zoom
- Easy installation and control



Specifications

| | |
|------------------------------|--|
| Projection System | DLP® |
| Native Resolution | XGA (1024 x 768) |
| Brightness | 5,000 AL |
| Contrast Ratio | 5,000:1 |
| Display Color | 1.07 Billion Colors |
| Lens | F=2.45~3.07, f=15.78 ~ 25.12 |
| Aspect Ratio | Native 4:3 (5 aspect ratio selectable) |
| Throw Ratio | 1.41~2.25 |
| Image Size (Diagonal) | 60"~240" |
| Zoom Ratio | 1.6X |
| Lamp Type | 370W |
| Lamp (Normal/Economic Mode)* | 2000/2500 hours |
| Keystone Adjustment | 2D, Vertical & Horizontal ± 30 degrees |
| Projection Offset | 107.5% ±2.5% |
| Lens Shift | Vertical: +7.5% |
| Resolution Support | VGA(640 x 480) to UXGA(1600 x 1200) |
| Horizontal Frequency | 15K~102KHz |
| Vertical Scan Rate | 24~120Hz |
| Compatibility | HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM |
| Interface | Computer in (D-sub 15pin) x 1 (Share with component) Monitor out (D-sub 15pin) x 1 Composite Video in (RCA) x 1 S-Video in (Mini DIN 4pin) x 1 HDMI x 2 (One with MHL) Audio in (Mini Jack) x 1 Audio L/R in (RCA) x 1 Audio out (Mini Jack) x 1 Speaker 20W LAN (RJ45) x 1 (LAN control) USB (Type Mini-B) x 1 (Download) USB (Type A) x 1 (5V/ 1.5A Power Supply) RS232 (DB-9pin) x 1 DC 12V Trigger x 1 IR Receiver x 2 |
| Dimensions (WxHxD) | 16.1" x 4.6" x 10.5" / 411.4x118.4x267.5 mm |
| Weight | 10.8 lbs / 4.9kgs |
| Power Supply | AC100 to 240 V, 50 to 60 Hz |
| Power Consumption | Typical 490W, Network standby <6W, Standby power <0.5W |
| Power Management Function | Automatic power off after 20 minutes without a display source. |
| Audible Noise | 36/33 dBA (Normal/Economic mode) |
| Languages | (28 Languages) |
| Picture Mode | Bright/Presentation/sRGB/Cinema/(3D)/User 1/User 2 |
| Accessories (Standard) | Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start Guide, Warranty Card, VGA(D-sub 15pin) Cable |
| Accessories (Optional) | Spare Lamp Kit P/N: 5J.JDP05.001 Ceiling Mount P/N: 5J.JAM10.001 3D Glasses P/N: 5J.J9H25.001 QP01 P/N: 5J.JCK28.A01 |
| UPC / Part # | 8400460-3265-4 / 9H.JDP77.15A |
| Limited Warranty | 3 Years Parts/Labor; 1 Year or 2,000 hours of lamp life |

Input and Output Terminals



- | | |
|-----------------------------|------------------------------|
| 1 LAN (RJ45) | 8 S-Video in (Mini DIN 4pin) |
| 2 RS232 (DB-9pin) | 9 Audio L/R in (RCA) |
| 3 USB (Type Mini B) | 10 Audio in/out (Mini Jack) |
| 4 USB (Type A) | 11 Monitor out (D-sub 15pin) |
| 5 HDMI-2 | 12 Composite Video in (RCA) |
| 6 HDMI-1 / MHL | 13 MIC |
| 7 Computer in (D-sub 15pin) | 14 12V Trigger |



*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



BenQ.us • BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

SX920 | 12415

BenQ

Because it matters